

Wireless Monitoring STX



Monitoring

Compact, reliable, accurate

The STX and SLTX transmitters use a highest precision temperature and humidity sensor which is accurate to +/-2% which is integral to the transmitter thus allowing for a smaller and neater outline.

Available in either a black or white enclosure the STX transmitter ensures discreet and reliable monitoring in display cases and public spaces as well as stores and archives.

The transmitter address and transmission intervals can be programmed by the user without the need for any further equipment and the units can be wall mounted or left freestanding for further flexibility. It uses standard off the shelf batteries which can be changed by the user.

If required the STX can be adapted to include a Lux and UV sensor (SLTX) and the display then shows a continuous flow of all four readings,. This provides a more cost efficient monitoring of all conditions in one compact unit.

The STX unit has a clear display which shows the current reading taken directly from the last transmission as well having a low battery warning and a transmission indicator providing important information at a glance.



TECHNICAL DATA

ACCURACY	2% RH and 0.2°C
RANGE	12 miles line of sight
BATTERY	4 x AA with a battery life of over 2 years
DIMENSIONS	85mm H x 70mm W x 40mm D, aerial 160mm weigh 257g inc batteries

Call: 01782 565917

Web: www.meaco.co.uk

Email: information@meaco.co.uk

meaco
measurement and control